

RAGLAN FLOAT (75/55)**Dimensions:**

Length	- 54'6"
Width	- 102"
Height	- 24" ground to top of deck
Weight	- Approximately 28,000 lbs.

Gooseneck:

Style	- Hydraulic removable, non-ground bearing
Cylinders	- Dual hydraulic cylinders, 10" bore
Steel	- 130,000 yield plate, 3/8" web, 1 1/2" x 4" flanges
Column Lock Pins	- 4" dia, hydraulic operated, 3 ride height setting
Hydraulic Power	- Tractor wet line
Swing Clearance	- 108"
Stinger Assembly	- Hydraulic cylinder on a tubular swing arm
'D' rings	- Two (2) at rear
Chain storage	- Access door at rear of gooseneck, chain rack w/ lockable doors

Deck:

Material	- 100,000 yield web and flanges
Dimensions	- 24'0" long x 8'6" wide x 24" high x 8" clearance
Main Rails	- 3/4" x 9" flanges c/w 3/8" web
Cross Sills	- 8" I-beam
Outer Rails	- 1/2" x 5" flanges x 12" deep
Floor	- 2" white oak
Pockets	- 3" x 4" pockets both sides, 20 provided
Out Riggers	- 22 provided, 12" fabricated swing type



RAGLAN FLOAT (75/55)**Rear Bridge (Removable):**

Axles	- Parallel spindle, 77 ½" track 25,000 lbs. capacity
Wheels	- 10 stud steel (long studs)
Brakes	- 16.5" x 7" x ¾" Q-brake, CM 20, S cam, cam enclosures
Air Chambers	- 30/30 brake chamber
Stroke Indicators	- Tattle Tail
ABS	- 4S/2M Haldex
Suspension	- Hendrickson HT-300-U @ 72" tridem
Lift Kit	- On rear axle only
Boom Well	- Open full length on rear bridge
Suspension Controls	- Mounted @ rear of trailer in a weather proof box - Raise, ride, dump
'D' Rings	- 6 provided and 6 on rear bridge
Tires	- 275/70R 22.5, 16 ply, Continental
Rims	- 8.25 x 22.5 10 hole hub pilot steel (white)

Miscellaneous:

Lights	- LED c/w side signal
Paint	- Sandblasted, primed, painted one (1) colour
Reflective Tape	- 2" wide conspicuity tape to M.O.T. specs

